




DECLARATION OF PERFORMANCE OF THE „ARPANEL” SANDWICH PANELS

NO. DWU/D MiWo/02/2022/EN

1	Name and address of manufacturer	Adamietz Sp. z o.o. 47 – 100 Strzelce Opolskie ul. Braci Prankel 1 Poland
2	Unique identification code of the product-type	Sandwich panels ARPANEL D 80/120 MIWO, ARPANEL D 100/140 MIWO, ARPANEL D 120/160 MIWO, ARPANEL D 150/190 MIWO, ARPANEL D 160/200 MIWO, ARPANEL D 180/220 MIWO, ARPANEL D 200/240 MIWO, ARPANEL D 220/260 MIWO with a core of mineral wool.
3	Intended use, in accordance with the applicable harmonized technical specification	Metal faced insulating panel for use in buildings as roofs.
4	System of assessment and verification of constancy of performance:	3
5	Harmonized standard	PN-EN 14509:2013 - 12
6	Notified body	– INSTYTUT TECHNIKI BUDOWLANEJ Warsaw - No. 1488 – IMA Materialforschung und Anwendungstechnik GmbH Dresden – No. 2456 – Fires s.r.o. Batizovce – No. 1396
7	Declared performances	Annex no. 1

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:


Jarosław Łoś
Prokurent

Strzelce Opolskie 16.11.2022

ARPANEL - Sandwich panels

Adamietz Sp. z o.o.

47-100 Strzelce Opolskie

ul. Braci Prankel 1

NIP [Tax Id. No.]: 756-18-36-633

REGON [Statistical Id. No.]: 532242263

tel. +48 77 463 00 55

fax. +48 77 463 92 00

email: biuro@arpanel.pl

District Court Of Law In Opole, 7th Commercial

Division, National Court Register No.: 0000100273

Share capital: 2.330.000,00 PLN

www.arpanel.eu



Annex 1 to the Declaration of performance NO. DWU/D MiWo/02/2022/EN

Panel thickness [mm]			80/120	100/140	120/160	150/190	160/200	180/220	200/240	220/260
Dimensional tolerances			± 2 %							
Mass [kg/m ²]			18,7	20,9	23,1	26,3	27,4	29,6	31,8	33,9
Density of core material (MIWO) [kg/m ³]			105±10%							
External/Internal Facing - Steel grade			S280GD+Z; S250GD+Z; S220GD+Z							
Coating type			SP25, Food Safe (PVC), PRISMA, HPS, HDX, INOX, PVDF, PUR/PA							
Thickness of facing material [mm]			External: 0,6 - 0,7				Internal: 0,5 – 0,7			
Facing profile			External: T				Internal: G, L, M20			
Cross panel tensile strength f _{ct} [kPa]			120	120	120	120	120	120	120	120
Compressive strength (core) f _{cc} [kPa]			70	70	70	70	66	58	50	50
Shear strength (core) f _{cv} [kPa]			45	45	45	45	44	42	40	40
Shear modulus (core) G _c [kPa]			4,4	4,1	3,9	3,5	3,4	3,1	2,8	2,8
Creep coefficient	t= 2.000 h		0,5							
	t= 100.000 h		1,0							
Wrinkling stress [MPa]	in span	external face	234	224	215	200	195	184	173	162
		external face >80°C	234	224	215	200	195	184	173	162
		internal face	98	94	89	83	82	79	77	75
	At central support	external face	234	224	215	200	195	184	173	162
		external face >80°C	234	224	215	200	195	184	173	162
		internal face	88	84	81	75	74	71	69	67
Thermal conductivity λ _D [W/m*K]			0,040							
Thermal transmittance U _{d,s} [W/m ² *K]			0,48	0,39	0,32	0,26	0,24	0,22	0,20	0,18
Reaction to fire			A2-s1,d0							
Fire resistance			NPD	RE 120; REI 90						
Fire-spread			Broof (t ₁)			Broof (t ₁), (t ₃)	Broof (t ₁)		Broof (t ₁), (t ₃)	Broof (t ₁)
Water permeability [class]			A							
Air permeability	Positive pressure		C = 1,2824; n = 0,1683							
	Negative pressure		C = 0,3920; n = 0,2373							
Airborne sound insulation			30 (-1;-3)					31 (-1;-3)		
Rw (C, C _{tr}) [dB]										
Sound absorption α _w			0,2							